# PHYSICAL

Weight	Without Battery: 133g	
	With Battery: 160g	
Size (H×W×D)	39.0 × 59.3 × 69.8mm	
Water Rating	Waterproof to 33 ft (10m)	
Temperature Range	Operating: 0 to 40°C (32 to 104°F) Cold Operation with Warmed Battery:  -20 to 40°C (-4 to 104°F); Battery at 25°C (77°F) Charging: 0 to 45°C (32 to 113°F)	
	Storage: -40 to 85°C (-40 to 185°F)	
Battery	Replaceable, Rechargeable Lithium-Ion 1250mAH, 3.8V, 4.7Wh Run Time: Stitched 4K 30FPS – 1 hour 5 minutes Unstitched 5K 30FPS – 1 hour 5 minutes	
Supported SD Cards	Micro SD Max Capacity: 128GB FAT32 (≤ <b>32GB), exFAT (≥ 32GB)</b> Write Speed ≥15MB/s. UHS-I, Class U3 Or Higher Rating Required <u>Click Here For Recommended Card List</u>	
Data Interface	Micro USB USB 2.0	
Video Output Port	Equirectangular, Stitched Output Resolution up to 4K at 30FPS (3840 × 2160)	
Status Display	Sunlight-visible, transflective memory-in-pixel (MIP) 1.00" x 0.42" (25.3 x 10.7 mm)	
VIDEO		
Lens Modes	360: Capture Stitched-In-Camera, Fully Spherical Videos In Equirectangular Format. Front Only: Capture Videos in Traditional Fixed-Frame Format Using the Front Lens. Rear Only: Capture Videos in Traditional Fixed-Frame Format Using the Rear Lens. RAW: Capture Unstitched, Fully Spherical Videos. Each Video produces 2 high-res files; 1 for each lens.	

Video Modes	5.7K*: 2880×2880 (2 files) / 30fps @ 120Mbps (60Mbps per file) : 360 Unstitched 5K: 2496×2496 (2 files) / 30fps @ 100Mbps (50Mbps per file) : 360 Unstitched 4K: 3840×2160 / 30fps @ 80Mbps : 360 Stitched 3.5K: 1760×1760 (2 files) / 60fps @ 100Mbps (50Mbps per file): 360 Unstitched FHD: 1920×1080 / 120fps @ 50Mbps: Traditional 16:9 FHD: 1920×1080 / 60fps @ 40Mbps : Traditional 16:9 Timelapse Video: Available in 4K and 5K Resolutions. Interval 2/5/10/30/60s * Requires Mobile App to enable. Run Times May Be Reduced.		
Stabilization Modes*	Stabilize: Smoothes out quick movements and vibrations and levels out the horizon Lock: Stabilizes and counteracts the camera orientation in full 360, locking the stabilized orientation to a specified direction. Follow: Stabilizes and counteracts the camera orientation in full 360, the stabilized orientation follows the GPS trajectory. * Stabilization applied during playback and in videos produced using VIRB mobile app or VIRB Edit desktop software. Available only for videos stitched in camera.		
Video Format	.MP4 (AVC / H.264 Encoding)		
Max Video Bitrate	120 Mbps		
ISO Range	100 – 1600 (Automatic) 100 – 6400 (Manual)		
Manual Settings*	ColorVivid or FlatWhite BalanceAuto or ManualSharpnessLow/Medium/HighISO Limit400/800/1600/3200/6400Exposure Bias± 2.0 EV RangeExposure LockEnable/DisableExposure BalanceBalanced Exposure/Front Lens Bias/Rear Lens Bias/Independent*Requires Mobile Approx		
РНОТО			
Lens Modes	360: Capture Stitched-In-Camera, Fully Spherical Photos In Equirectangular Format.		

360: Capture Stitched-In-Camera, Fully Spherical Photos In Equirectangular Format. Front Only: Capture Photos in Traditional Fixed-Frame Format Using the Front Lens. Rear Only: Capture Photos in Traditional Fixed-Frame Format Using the Rear Lens. RAW: Capture Unstitched, Fully Spherical Photos. Each Photo produces 2 high-res files; 1 for each lens.

Photo Resolution	15MP: 5640 × <b>2816 (Stitched 360)</b> 2 × 9MP: 2 × 3008 × 3000 (Unstitched 360, 2 Files) 3MP: 1920 × 1440 (Traditional, Single Lens)	
Photo Modes	Single Shot Capture Burst Shooting: 20 frames / sec Auto Exposure Bracketing (AEB): 3 bracketed frames at <b>±1.0</b> EV Bias. Adjustable with App. Time Lapse: Interval 2/5/10/30/60 s Travelapse: Interval 0.01 miles and up. Requires Mobile App.	
Photo Format	.JPEG	
ISO Range	100 – 800 (Automatic) 100 – 800 (Manual)	
Timer Delay	2, 5, 10, 30 or 60 seconds. Only applies to first photo captured when set to Time Lapse.	
Manual Settings*	Color White Balance Sharpness ISO Limit Exposure Bias Exposure Balance *Requires Mobile App	Vivid or Flat Auto or Manual Low/Medium/High 100/200/400/800 ± 2.0 EV Range Balanced Exposure/Front Lens Bias/Rear Lens Bias/Independent

# AUDIO

Format	48 kHz Sampling, AAC Compression, 4-Channel Ambisonic		
Spatial Output	Planar, 4-Channel First-Order Ambisonic (ACN Ordering, SN3D Normalization)		
Gain Control	AGC (Automatic Gain Control)		
Internal Microphones	MEMS - Waterproof, Rugged, Exposed for sensitive audio capture		
Wireless Microphone	Bluetooth - Mono, upsampled to 48kHz		
	Mixed Output: Combined omnidirectional (mono) Bluetooth mic with ambisonic/environmental audio		

# OPTICS

Sensor

1/2.3" Backside-Illuminated CMOS Sensor Count: 2 Pixel Count: 12MP per Sensor Pixel Size: 1.55 um

Lens	8-Elements, Replaceable Strengthened Glass Cover Lens
	Lens Count: 2
	FOV (Unstitched): 201.8° per Lens
	FOV (Traditional 16:9): 141º Horizontal
	Depth of Focus: 40cm to ∞
	Effective Focal Length: 1.036mm
	35mm Equivalent Focal Length: 6mm
	Fixed Aperture: f/2.0

Electronic Shutter Speed30 - 1/8000s

# SENISORS AND ALIGMENTED REALITY (A/R)

SLIISONS AND AU	OWILINIED REALITY (AVR)
On Board Sanaara	CDC + CLONASS, 10 Uz location conture

On-Board Sensors	GPS + GLONASS: 10 Hz location capture Barometer: Elevation capture Accelerometer: Force and Motion capture Gyroscope: Rotation capture Compass: Bearing capture
A/R Data Overlay Settings	Vehicle Mode: Lock Overlays to the mounted subject, even when stabilization is enabled Fine Adjustment Tools: Scale, Tilt, Rotate, Color
A/R Data (Camera Collected)	SpeedDistanceAltitudeRelative ElevationG-ForceJump Metrics: Hang Time, Jump Height, Jump Distance, Rotations in Air, Jump CountGradeVertical SpeedPacePitchRollCourseBearingGPS CoordinatesTrack Shape and PositionLap Times (Automatic/CC, Manual)Lap Count (Automatic/CC, Manual)

Accessory: Pulse	Heart Rate: Instantaneous, Average, Minimum, Maximum and Graphing Compatible Products: <u>vivosmart HR /</u> <u>vivosmart HR+</u> <u>vivoactive HR</u> <u>fenix 5</u> <u>fenix 3HR</u> <u>HRM-RUN</u> <u>HRM-TRI</u>
Accessory: Running Metrics	Heart Rate: Instantaneous, Average, Minimum, Maximum and Graphing Vertical Oscillation: Instantaneous, Average, Minimum, Maximum and Graphing Ground Contact: Instantaneous, Average, Minimum, Maximum and Graphing Compatible Products: <u>HRM-RUN</u> <u>HRM-TRI</u>
Accessory: Ambient Temp	Temperature: Instantaneous, Average, Minimum, Maximum and Graphing Compatible Products: <u>tempe</u>
Accessory: Cycling Metrics	Power: Instantaneous, Average, Minimum, Maximum and Graphing Speed: Instantaneous, Average, Minimum, Maximum and Graphing Cadence: Instantaneous, Average, Minimum, Maximum and Graphing Compatible Products: <u>Vector</u> <u>Bike Speed Sensor</u> <u>Bike Cadence</u> <u>Sensor</u>
Accessory: Vehicle Metrics	Vehicle Speed Engine RPM Engine Load Engine Torque Engine Fuel Rate Engine Coolant Temperature Throttle Position Intake Air Temperature Mass Air Flow Rate Compatible Products:

OBDLink LX Other ELM-327 Compatible Sensors

Accessory: Flight Metrics Position Altitude Course Over Ground Pitch Roll Lateral Acceleration Normal Acceleration Turn Rate Compatible Products: G3X Touch FlightStream 110/210 Accessory: Boating Metrics Engine Data: Engine Speed, RPM Wind Data: Apparent Wind Angle, Apparent Wind Speed, True Wind Angle, True Wind Speed Water Data: Water Depth, Water Temperature, Speed Through Water Compatible Products: GPSMAP 74XX / 76XX GPSMAP 84XX / 86XX Engine Data: Requires NMEA 2000 accessory Wind Data: Wind Sensors Water Data: Transducer

#### WIRELESS

Wi-Fi	802.11 b/g/n	
	Mobile App Connection	
	Local Area Network Conection	
NFC	Passive	
	Location: Top, Center of Camera, Under the Display	
ANT+	Garmin Remote and Sensor Connectivity	
	Compatible Remotes:	
	VIRB Remote	
	Fenix 5 Series	
	Fenix 3 Series	
ANT+	Garmin Remote and Sensor Connectivity Compatible Remotes: VIRB Remote Fenix 5 Series	

	vivoactive HR / HR vivosmart Forerunner 935 Edge	÷
Bluetooth	Bluetooth 4.0 Sensor Connectivity Wireless Headset Micro Recommended Headset Jabra Extreme 2 BlueAnt Q3 BlueParrott B250-2 Plantronics M55	S:
Voice Control	OK Garmin Start Recording Stop Recording Take a Picture Remember That Enable/Disable Wi-Fi	Activation Phrase Begin recording video in the currently selected mode Stop recording video Capture a photo or set of photos in the currently selected mode Tag the video at that point in time for fast recall later (Only While Recording) Turn Wi-Fi On or Off
APP	Supported Languages:	English(US, UK), French, Italian, German, Spanish, Swedish, Japanese, Mandarin
AFF		
Mobile App	VIRB Mobile	
Streaming Playback	Equirectangular, Stitched Up to 1280 × 720 at 30FPS	
Live Stream	Supported Devices: iOS 10.0 or Later Format: Equirectangular, Stitched YouTube: Up to 1280 × 720 at 30FPS at up to 5Mbps Facebook: Up to 1280 × 720 at 30FPS <b>at up to 5Mbps</b>	
Required Operating System	iOS 10.0 or Later Android 5.0 or Later	
Recommended for 4K sharing	iPhone SE iPhone 6 / 6 Plus	

iPhone 7 / 7 Plus iPad Air 2 Samsung S7 / S7 Edge Google Pixel / Pixel XL Sony Z5

# DESKTOP SOFTWARE

Application Name	VIRB Edit	
Minimum Requirements	Operating System (PC) Operating System (Mac) Processor Memory (RAM) Graphics Card Graphics Memory (RAM) Display Resolution Storage	2.5GHz Quad-Core Intel Core i7 or AMD FX 8 GB Intel HD 5000 / nVidia GeForce GT 630 / AMD Radeon 8570
Recommended Configuration	Operating System (PC) Operating System (Mac) Processor Memory (RAM) Graphics Card Graphics Memory (RAM) Display Resolution Storage	3.0GHz Quad-Core Intel Core i7 or AMD FX 16 GB Intel HD 530 / nVidia GeForce GTX 960 / AMD Radeon R9 380