

LUMISHORE® THRU-HULL LIGHTING GUIDE

Our premium thru-hull underwater lights are constructed from durable, marine-grade aluminum bronze and are purpose-built for GRP superyachts that need high output lighting with extra-wide beam angles.

	TIX804	TIX804	TIX1604	TIX1604
Series	EOS	SUPRA	EOS	SUPRA
Fixture (lumens)	12,000	13,500	17,500	20,000
Beam angle (degrees)	110	110	110	110
AC input voltage range (volts)	90–240	90–240	90–240	90–240
Optional 12- or 24-volt DC drivers	✓	✓	✓	✓
Max AC current draw (amps)	1.2	1.2	1.8	1.8
Light diameter (mm)	120	120	140	140
Shaft length (mm)	184	184	184	184
Installation location	Transom, side, bottom	Transom, side, bottom	Transom, side, bottom	Transom, side, bottom
Colors	Full color	Blue & white	Full color	Blue & white
Color cycle	✓		✓	
Strobe mode	✓	✓	✓	✓
Fade	✓	✓	✓	✓
Controller	STV2203-i, STV2204-i + EOS-LUX Command Center, third-party DMX controllers	On/off color select switch	STV2203-i, STV2204-i + EOS-LUX Command Center, third-party DMX controllers	On/off color select switch